

# ステンレス熱間不等辺アングル

## SUS304

サイズ	kg/P	断面特性									
		304	断面積 (cm <sup>2</sup> )	重心の位置 (cm)		断面二次モーメント (cm <sup>4</sup> )		断面二次半径 (cm)		断面係数 (cm <sup>3</sup> )	
t x A x B	6,000	a	Cx	Cy	Ix	Iy	ix	iy	Zx	Zy	
4 x 45 x 30 ◎	13.6	2.866	1.48	0.740	5.78	2.05	1.42	0.846	1.91	0.908	
6 x 50 x 30 ◎	21.4	4.487	1.74	0.788	10.7	2.97	1.54	0.813	3.27	1.34	
6 x 65 x 50 ◎	31.7	6.661	2.01	1.30	27.1	14.2	2.02	1.46	6.03	3.85	
6 x 75 x 50 ○	34.4	7.227	2.42	1.20	40.4	14.3	2.37	1.41	7.97	3.77	
6 x 75 x 65 ◎	38.8	8.161	2.18	1.72	44.2	31.4	2.33	1.96	8.30	6.57	
6 x 100 x 75 ○	48.8	10.25	3.01	1.79	102	49.5	3.16	2.20	14.7	8.67	
6 x 125 x 75 ○	55.9	11.75	4.05	1.60	190	52.4	4.02	2.11	22.5	8.89	
7 x 75 x 50 ○	39.5	8.308	2.46	1.24	45.8	16.1	2.35	1.39	9.08	4.28	
7 x 100 x 75 ◎	56.7	11.92	3.05	1.86	118	58.6	3.15	2.22	17.0	10.4	
9 x 75 x 50 ◎	50.0	10.52	2.53	1.33	56.4	20.5	2.32	1.40	11.3	5.60	
9 x 90 x 75 ◎	67.2	14.18	2.73	2.03	109	70.4	2.77	2.23	17.4	12.9	
9 x 100 x 75 ○	71.4	15.00	3.14	1.91	146	70.2	3.12	2.16	21.3	12.6	
9 x 125 x 75 ○	82.2	17.25	4.19	1.72	274	74.5	3.98	2.08	32.9	12.9	
9 x 150 x 90 ○	99.0	20.85	4.97	2.00	483	133	4.81	2.53	48.2	19.0	
12 x 150 x 90 ○	130.0	27.42	5.09	2.12	626	171	4.78	2.50	63.2	24.8	

○…圧延品, ◎…切断品